

Article-No.:	Model Name:
---------------------	--------------------

508695-0 **Patron® REVOLUTION long cuff**

Design & Konstruktion:

Description: The models of the Patron® range stand out due to their wide variety and very broad field of application in the area of leather gloves. Proven in use 100,000 times. The Patron® REVOLUTION is suitable for use in direct firefighting (flashover, inside attack) as well as recovery, rescue and technical assistance within the meaning of DIN EN 659:2008 (DIN EN 659+A1+AC:2009). Absolute fit accuracy within the sizes and high dexterity due to anatomical and threedimensional cut.




Sizes: 6 – 13
Colours: 7149 black/red

Materials:

Palm, backhand: Special nappa calfskin, heat-resistant, water-repellent, tanned to be shrink-optimized, special softness due to the selected greases, **washable up to 60 degree**
Palm: Additionally reinforced with elastic knitwear Kevlar with carbon/silicone coating
Finger layers: Special nappa calfskin, heat-resistant, water-repellent, tanned to be shrink-optimized, special softness due to the selected greases, washable up to 60 degree
Internal lining: 3 -D -performance lining, consisting of aramid
Cuff: Split cowhide, cuff end with nappa calfskin, adjustable strap with flap and Velcro® closure
Insert: Hipora moisture barrier, waterproof, windproof, breathable
Applications: Reflex stripes yellow on cuff 50 mm, wet reflective, ring and carabiner hook, label „PATRON REVOLUTION“ and „DAS ORIGINAL“ on end of cuff

Product instructions:

Cleaning: For drying hang up on the fingertips 

Recommendation: In order to ensure the durability of the glove, we recommend the use of commercially available cleaning detergents. The gloves must be checked for integrity before they are used again.

Restriction: Do not tumble dry, do not spin, dry clean requires prior advice from a recognized professional. For changes to the properties the manufacturer is not able to accept any liability here.

Service life: The service life of glove depends on degree of wear and use of intensity in field of application. There is no possibility to give some information about service life.

Storage / disposal: Store the gloves in a dry, light-protected and clean place. Damaged or no longer required gloves can be disposed of with household waste.

Pictograms and power levels according to DIN EN 659:2008 (DIN EN 659+A1+AC:2009) CAT III

Parameter	Requirement	Result	Level
A = Abrasion (DIN EN 388)	min. 3	2100 Cycles	3
B = Cut resistance (Coupe-Test) (DIN EN 388:2016, Abs. 6.2.6.)	min. 2	12,5 Index	5
E = Cut resistance DIN EN ISO 13997 is not applicable			x
C = Tear resistance (DIN EN 388)	min. 3	52 Newton	4
D = Puncture resistance (DIN EN 388)	min. 3	104 Newton	4
A = Burning behavior (DIN EN 407)	min. 4	Burning time / Glowing time=0	4
Dexterity (DIN EN 420)	min. 1	Test pen 5mm	5
Convective heat resistance (DIN EN 367)	HTI ₂₄ ≥ 13	Back 48 Palm 27	-
Radiant heat resistance (DIN EN ISO 6942)	RHTI ₂₄ ≥ 20	Mean value 44	-
Contact heat resistance (DIN EN 702)	t _c ≥ 10s	Dry 17 Wet 11	-
Seam breaking strength (DIN EN ISO 13935-2)	min. 350 N	970 Newton	-



3544X



PSA-regulation (EU) 2016/425

Performance levels according to DIN EN ISO 13997:

	Performance levels					
	A	B	C	D	E	F
E = Cut resistance (N)	2	5	10	15	22	30

Testing: 0624 – Centro Tessile Contoniero e Abbigliamento S.p.A. P.zza Sant Anna, 2 21052 Busto Arsizio (VA) - Italy

Contact: askö GmbH – Innovative Schutzausrüstung Adolph-Kolping-Str. 6, D – 72393 Burladingen Tel: 07475 / 95000-0 Fax: 07475 / 9500-29 E-Mail: info@askoe-online.de Website: www.askoe-online.de

1 or rather A = low level; 4, 5 or rather F = high level; x = not examined

Performance data according to DIN EN 388 – mechanical risk

Audit	Level 1	Level 2	Level 3	Level 4	Level 5
A = Abrasion resistance (number of cycles)	100	500	2000	8000	-
B = Cut resistance (Index) Coupe Test	1,2	2,5	5,0	10,0	20,0
C = Tear resistance (N)	10	25	50	75	-
D = Puncture resistance (N)	20	60	100	150	-

For the declaration of conformity please visit www.askoe-online.de